



AI@Edge Fanless Compact Embedded BOX PC with Intel® Celeron or Pentium™ processor and One Myriad™ X

Front View



Rear View



## Features

- Design for AI@Edge application
- Built in Intel® Movidius™ Myriad™ X, support AI computing
- Slim Boxer Design: 35mm
- Rich I/O, Design for Auto System Control
- Gigabit Ethernet x 2, USB3.0 x 4
- Support Wallmount




## Specifications

System	
CPU	Intel® Celeron/Pentium™ processor
Chipset	Intel® System on Chip
System Memory	DDR3L SO-DIMM slot x 1 Supports 1867 MHz and up to 8GB
AI Solution	Intel® Movidius™ Myriad™ X x 1
Display Interface	HDMI 1.4 VGA
Storage Device	mSATA
Ethernet	10/100/1000 Base-TX x2
I/O	Power Button x 1 USB Type A x 4 for USB3.0 HDMI type A x 1 for HDMI v1.4b RJ45 x 2 for GbE LAN with LED indicator (i211-AT x2) Power Input x 1 3-pin terminal block in default (+, -, GND) Co-layout Mic-in x 1, Line-out x 1 DB-9 x 3 for RS-242/422/485 (Switch by BIOS) DB-15 x1 for VGA Remote On/Off Antenna Holes x 2 DC-in 3-pin terminal block(9~24V) x1
Expansion	Full-size Mini PCIe slot x 1 (Intel® Movidius™ Myriad™ X) Half-size Minicard slot x 1 (mSATA only)
Indicator	Power LED x1, HDD active LED x1
OS Support	Debian 9.8
Power Supply	
Power Requirement	3 Pin 9-24V DC-in terminal block
Mechanical	
Mounting	Wallmount
Dimensions (W x H x D)	6.54" x 4.2" x 1.38" (166mm x 106.6mm x 35mm)
Gross Weight	3.6 lb (1.6kg)
Net Weight	1.3 lb (0.6 kg)
Environmental	
Operating Temperature	-13°F ~ 131°F (-25°C ~ 55°C) with W.T. mSATA (according to IEC68-2-14 with 0.5 m/s AirFlow; with industrial decives)
Storage Temperature	-4°F ~ 158°F (-20°C ~ 70°C)
Storage Humidity	95% @ 40°C, non-condensing
Anti-Vibration	3 Grms/ 5 ~ 500Hz/ operation – mSATA
Certification	CE/FCC class A

## Dimension

Unit: mm



## Ordering Information

Part Number	CPU	PCH	RAM	LAN	USB 3.0	USB 2.0	RS-232	RS-232/422/485	Digital I/O	Audio	Storage	Display	AI Solution	Mounting	Power	Operation temp.
BOXER-8310AI-A1-1010	N3350	SoC	—	2	4	—	—	3	—	MIC-in, Line-out	Half size miniCard for mSATA x1	VGA/ HDMI x1	Intel® Movidius™ Myriad™ X x 1	Wallmount	9~24V	-25°C ~ 55°C
BOXER-8310AI-A2-1010	N4200	SoC	—	2	4	—	—	3	—	MIC-in, Line-out	Half size miniCard for mSATA x1	VGA/ HDMI x1	Intel® Movidius™ Myriad™ X x 1	Wallmount	9~24V	-25°C ~ 55°C

## Packing List

- Wallmount Bracket x 2
- 3 Pin DC-in Power Connector x 1
- BOXER-8310AI

## Optional Accessories

- 1255300402  
40W Power Adapter
- 1702031802  
Power Cord (US type)
- 1702031803  
Power Cord (European Type)
- 170203180E  
Power Cord (Japanese Type)
- 9741640404  
Din Rail Mount Kit